

### NGA-701

Addressable Input/Output Module



### OVERVIEW

The Addressable NGA-701 Input/Output Module is a fully monitored device which permits the interfacing of third party equipment with the Fire Alarm control Panel using normally open dry contact connections while also providing a changeover output relay to control ancillary equipment. The Green LED will pulse every time the unit is polled by the panel. The yellow LED will be On whenever there is a fault condition in the module and finally the Red LED will be On when there is an alarm condition at the module's NGA-701.



The connection to the NGA-701 is monitored for Fault (open or short circuit) and Alarm conditions. The output relay can be powered from the detection loop (default) or optionally by an external 24V DC supply. Relay operation is confirmed by an onboard Yellow LED. The interface is used to monitor the contacts of an external system which must be interfaced to the Fire Alarm System, for example a flow switch in a sprinkler system to indicate if the sprinkler have been activated or extinguish and level monitoring in Gas Extinguishing Systems etc.

The Output relay can be programmed to close fore doors, activate smoke removal systems etc. the factory default setting is for the relay to receive its operating power from the loop. When in this operating mode the on board 2-way DIL switch has both switches in the On position. If the relay output is to be powered by an external supply, then both switches should be in the OFF position. In this case the coil of the relay output is completely isolated from the loop.

An 8 way DIL switch is provided to configure the module's address. This value can be set in the range 1 to 125.

### SPECIFICATION

Specifications	
SUPPLY VOLTAGE	Loop Powered - 17 V to 30 V DC
LOOP CURRENT - QUIESCENT	I/P: OK 0.46 - FLT OC 0.33 - FLT SC 0.79 mA
LOOP CURRENT - ALARM LED ILLUMINATED	2.0 mA + 9.8 mA with Relay Active
MAX. CABLE SIZE	2.5 mm <sup>2</sup>
MAX. HUMIDITY	95% RH Non-Condensing
OPERATING TEMPERATURE	0°C to 50°C
DIMENSIONS	100 (D) x 48 (H) mm
WEIGHT - MODULE	29 g
WEIGHT - BOXED	134 g

Order Code	
NGA-701	ADDRESSABLE INPUT/ OUTPUT MODULE