

PRODUCT DATA SHEET

RE-716LSS

Addressable Loop sounder
with Flasher (Weatherproof)



OVERVIEW

The RE - 716LSS range of addressable sounder base are designed to be connected to analogue addressable Fire Alarm Systems and these loop sounder base should be connected to the compatible control panel. The RE-716LSS loop sounder base receives their power from analogue addressable communication loop and it is controlled via addressable communication. The address of these device should be in the range of 128 to 159 addresses and it shall be set by 8 way DIP switch.



FEATURES

- ▶ Addressing by 8 way DIP switch
- ▶ Low Standby Current
- ▶ Slim and Sleek
- ▶ Sweep tone

OPERATING SPECIFICATION

Operating Voltage	: 17 ~ 28 VDC
Operating Current	: 7 mA
Standby Current	: 0.5 mA
Sound level	: 95db @1m
Sound Type	: Piezo Electric Type
Tone Type	: Sweep tone
Material	: FR ABS
Operating Temperature	: 0°C to 49°C / 32°F - 120°F
Operating Temperature	: -10°C to 70
IP (standard / indoor)	: IP-42 (716LSS)
IP (weather proof / outdoor)	: IP-65 (716 LSS)
Colour	: Red
Mount Type	: Surface mount / Flush mount
Dimension	: 100mm Dia