



## SEMM - 2 EMERGENCY LIGHTING MONITORING CONTROL PANEL



### Features:

- \* Status of battery
- \* Status of Lamp
- \* Charge condition
- \* Function Test
- \* Duration Test
- \* Group Testing
- \* Inhibit Mode

### Technical Data:

- \* Rated Voltage and Frequency : 230V @ 50/60Hz, consuming 6.0W total
- \* Temperature Range : 0°C to +50°C
- \* Weight : 873g without power supplies and controls
- \* Dimensions WxHxD(mm) : 213x150x35 (including surface mount housing)
- \* Cutout size (mm) : 198 x 117
- \* Protection Rating : IP20 - suitable for indoor use only
- \* Number of Dali lines : 2
- \* Emergency lights per line : 64
- \* Mounting way : Wall mounting
- \* Memory capacity : 4 years of report storage

### Cable requirements:

- \* USB : For upgrading not for end user use
- \* AC input : 2-core TPS twin 1.5mm<sup>2</sup> minimum
- \* Relay : Extension to inform failure
- \* Network : Cat 5e Ethernet cable RJ45
- \* Dali1 and 2 : 2-core (main rated) 1.0 to 1.5mm<sup>2</sup> (200 mtrs and 300 mtrs respectively)