



RE-HLW46W CEILING OR WALL MOUNT SPEAKER SPEAKER/STROBES

Applus⁺

Description:

The RE-HLW46W Series are ceiling or wall mount, selectable candela speakers and speaker/strobes designed to meet code requirements for audio, visual and voice communications. The RE-HLW46W Series are quality speaker products that offer both dependable evacuation signaling and visual alarms, or a combination of both. The high output tamperproof candela selections are 15, 30, .75, 95 and 115

The RE-HLW46W Series can be mounted in a 2-1/8" deep square backbox, no extension ring .is needed

The RE-HLW46W Series provides a 25 or 70.7 VRMs speaker with field selectable power taps of 1/8W, 1/4W, 1/2W, 1W, 2W or 4W. The FG-SP4W strobes can be synchronized by using the Evax Synchronization Control Module or with FACP's that include the Gentex synchronization .protocol

The RE-HLW46W Series provides you a 25 or 70.7 VRMS speaker with field selectable power taps of 1/8W, 1/4W, 1/2W, 1W, 2W, or 4W and high output tamperproof candela selections of 15, 30, .75, 95 and 115



Input Watts	Speaker dBA @ 10 ft.	
	25 Volts	70 Volts
1/8	74.6	73.7
1/4	77.7	76.7
1/2	80.5	79.6
1	83.1	82.5
2	85.6	85.4
4	87.9	87.9

Features:

- Tamperproof Selectable Candela Selections of 15, 30, 75, 95 and 115.
- Unit Dimension: 6.1" Square X 1.88" Deep
- Ceiling Mounting to a standard 4" X 2-1/8" Deep Backbox - No Extension Ring Required
- High Quality dBA Output (Intelligible)
Frequency Range 400-4000Hz
- Screw Terminals, Separate In/Out Wiring (12-18 Gauge)
- Field Selectable Power Taps: 1/8W, 1/4W, 1/2W, 1W, 2W, 4W
- Speaker Voltage 25 or 70.7 VRMS Standard, Field Selectable
- To Synchronize Use the Evax Synchronization Control Module
- Tamperproof Grill
Faceplate Available in Red or Off-White
- Xenon Strobe Maintains Constant Flash Rate (1Hz) Regardless of Input Voltage

SSPKCLP CEILING MOUNT STROBE CURRENT RATINGS					
Candela	15cd	30cd	75cd	95cd	115cd
24 VDC	72mA	88mA	176mA	200mA	214mA

